More than just render...





The flexible acrylic texture coating that lasts







Performance Coatings for Masonry



^{*}Feature colour available only with AcraShield system topcoat. Printed colours are as close as practical to actual colours - refer to actual samples for exact colour.

When specifying your new home, insist on Flexible Acrylic Texture - not just painted render cement. The *Dulux AcraTex* acrylic texture system encapsulates walls in a high build, flexible skin which acts as a barrier against the elements, protecting your investment for years longer.

Dulux AcraTex products are designed to be used in system as specified in relevant Product Data Sheets and Approved Dulux Specifications. A 15 year material warranty is provided when a Full Dulux AcraTex system including 2 coats of AcraShield is applied by an AcraTex registered Applicator. If the product does not perform as specified, unless otherwise detailed, we will replace the goods free of charge. To make a claim under warranty, please contact Customer Service by telephone or post using the contact details provided on the product label. You must show proof of purchase and bear all expenses incurred in making a claim. The benefits of this warranty are in addition to other rights and remedies under any applicable law. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for

COLOUR & STYLE with Acrylic Texture Durability ——

Suggested Colour Selection



Suggested Colour Selection



Suggested Colour Selection



Upgrade to AcraShield® barrier coat protection

Lasts

High build acrylic texture provides more protection than just render

Lasts Longer

A *Dulux AcraShield* topcoat extends the total system weatherproofing performance

Lasts Longest

Ultimate system performance extends your system weatherproofing to 15 years with 2 coats of *AcraShield*

How Acrylic Texture lasts longer

When specifying a new project, insist on FLEXIBLE ACRYLIC **TEXTURE**, not just painted cement render.

The AcraTex 3 step system encapsulates the walls in a membrane envelope acting as a barrier against adverse weather conditions for years longer than cement render.

Available across the full Dulux® Exterior colour range.

The AcraTex System with it's flexible Acrylic Texture coating quards against degradation. Ordinary cement render is hard and brittle leading to typical problems like these.



CRACKING

Cement shrinks as it hardens & expands/contracts with temp. Low build paint systems are typically unable to bridge render cracking.



EFFLORESCENCE


Salt blooming over the surface & concentrated leaching at cracks can occur leading to discolouration and potentially peeling.



STAINING

Inferior paint systems hold dirt & can allow moisture ingress. Moisture attracts and magnifies surface contaminants.

The AcraTex® 3-step coating system



Suitably prepared masonry substrate (refer to *AcraTex* system guides for detail)

AcraTex AcraPrime[™]

More than just a "first coat" AcraPrime consolidates the substrate providing a stable base for long term integrity

AcraTex Coventry[™] (Range)

High Build Acrylic Texture up to 40 times thicker than paint, providing feature style and Acrylic Texture durability with colour integrated throughout.

AcraTex AcraShield®

Elastomeric Barrier coat protection up to 3 times thicker than paint – *AcraShield* is the system lock that ensures maximum resistance to the elements and extended system life cycle.



For further information go to: acratex.com.au

Dulux Customer Service: 13 23 77





